

CADILLAC

Vehicle Make	Year Range	Manufacturer of Axle	Axle Model	Spline Count	Cover Bolts	Special Notes	POWERTRAX No-Slip Traction System	
							Open	Limited-Slip
All Passenger Models (Unless listed separately below)								
Rear Axle								
	1991 - 1996	GM	8.5" rg	28	10		92-0785-2805	
	1991 - 1996	GM	9.5" rg	33	14		92-0795-3305	
	1988 - 1990	GM	7.625" rg	26	10	w/o Towing	92-0776-2605	
	1987 - 1990	GM	8.5" rg	28	10	Towing/Armored opt.	92-0785-2805	
	1985 - 1987	GM	7.5" rg	26	10	w/o Towing	92-0775-2605	
	1984	GM	8.5" rg	28	10	Round cover	92-0785-2805	
	1982 - 1984	GM	7.5" rg	26	10	DeVille/Fleetwood Brougham	92-0775-2605	
	1977 - 1984	GM	8.875" rg	30	12	Comercial Chassis	92-0788-3005	
	1977 - 1983	GM	8.875" rg	30	12	Deville cutout cover	92-0788-3005	
	1977 - 1982	GM	8.875" rg	30	12	Fleetwood Brougham	92-0788-3005	
	1970 - 1976	GM						
Seville								
Rear Axle								
	1976 - 1979	GM	8.5" rg	28	10		92-0785-2805	
Escalade								
Front Axle (see notice at bottom of page)								
	1999 - 2000	GM	8.2" rg	28		IFS w/6 Lug		
	1999 - 2000	GM	9.2" rg	33		IFS w/turbo diesel	92-0792-3301	
Rear Axle								
	1999 - 2000	GM	8.5" rg	30	10		92-0785-3005	

NOTICE REGARDING ACCURACY OF THIS GUIDE:

Powertrax has attempted to make this Application Guide as accurate as possible. However, Powertrax cannot guarantee correctness. Identical model vehicles may have different axles or differentials than stated in this guide depending on original options ordered and other factors. It is advisable to check the vehicle to determine precisely which differential and axle are present. **IF YOU HAVE ANY QUESTIONS, PLEASE DON'T HESITATE TO CONTACT US AT 800-578-1020.**

NOTICE REGARDING FRONT AXLE APPLICATIONS:

The Powertrax No-Slip Traction System works well on the front axle of 4-wheel drive vehicles provided a couple of important guidelines are followed. The Powertrax No-Slip Traction System should be used only on vehicles equipped with locking hubs on the front axle or with front axle disconnect. In addition, the vehicle must not be equipped with full time 4-wheel drive. Vehicles equipped with a Powertrax No-Slip Traction System on the front axle should not be operated on the highway with the front hubs locked and 4-wheel drive engaged. Following these guidelines will ensure very on-road driveability while still providing maximum off-road traction.