

CADILLAC

Vehicle Make	Year Range	Manufacturer of Axle	Axle Model	Spline Count	Cover Bolts	Special Notes	Lock-Right Open
All Passenger Models (Unless listed separately below)							
Rear Axle							
	1991 - 1996	GM	8.5" rg	28	10		1920
	1991 - 1996	GM	9.5" rg	33	14		1950
	1988 - 1990	GM	7.625" rg	26	10	w/o Towing	1932
	1987 - 1990	GM	8.5" rg	28	10	Towing/Armored opt.	1920
	1985 - 1987	GM	7.5" rg	26	10	w/o Towing	1930
	1984	GM	8.5" rg	28	10	Round cover	1920
	1982 - 1984	GM	7.5" rg	26	10	DeVile/Fleetwood Brougham	1930
	1977 - 1984	GM	8.875" rg	30	12	Comercial Chassis	1910
	1977 - 1983	GM	8.875" rg	30	12	Deville cutout cover	1910
	1977 - 1982	GM	8.875" rg	30	12	Fleetwood Brougham	1910
	1970 - 1976	GM					
Seville							
Rear Axle							
	1976 - 1979	GM	8.5" rg	28	10		1920
Escalade							
Front Axle (see notice at bottom of page)							
	1999 - 2000	GM	8.2" rg	28		IFS w/6 Lug	
	1999 - 2000	GM	9.2" rg	33		IFS w/turbo diesel	1950
Rear Axle							
	1999 - 2000	GM	8.5" rg	30	10		1921

NOTICE REGARDING ACCURACY OF THIS GUIDE:

Powertrax has attempted to make this Application Guide as accurate as possible. However, Powertrax cannot guarantee correctness. Identical model vehicles may have different axles or differentials than stated in this guide depending on original options ordered and other factors. It is advisable to check the vehicle to determine precisely which differential and axle are present. **IF YOU HAVE ANY QUESTIONS, PLEASE DON'T HESITATE TO CONTACT US AT 800-578-1020.**

NOTICE REGARDING FRONT AXLE APPLICATIONS:

The Powertrax Lock-Right Locker works well on the front axle of 4-wheel drive vehicles provided a couple of important guidelines are followed. The Lock-Right Locker should be used only on vehicles equipped with locking hubs on the front axle or with front axle disconnect. In addition, the vehicle must not be equipped with full time 4-wheel drive. Vehicles equipped with a Lock-Right Locker on the front axle should not be operated on the highway with the front hubs locked and 4-wheel drive engaged. Following these guidelines will ensure very on-road driveability while still providing maximum off-road traction.