

# MAZDA

Vehicle Make	Year Range	Manufacturer of Axle	Axle Model	Spline Count	Cover Bolts	Special Notes	POWERTRAX No-Slip Traction System	
							Open	Limited-Slip
<b>Navajo</b>								
Front Axle (see notice at bottom of page)								
	1991 - 1994	DANA	Model 28	23	12			
Rear Axle								
	1991 - 1994	FORD	8.8" rg	31	10		<b>92-0688-3108</b>	<b>92-0688-3128</b>
<b>Pick-Up</b>								
Front Axle (see notice at bottom of page)								
	1998 - 2000	DANA	Model 35	27	10		<b>92-0435-2701</b>	
	1991 - 1994	DANA	Model 28	23	12			
Rear Axle								
	1994 - 2000	FORD	8.8" rg	31	10	4.0 V6	<b>92-0688-3108</b>	<b>92-0688-3128</b>
	1994 - 2000	FORD	7.5" rg	28	10	3.0 V6		

## NOTICE REGARDING ACCURACY OF THIS GUIDE:

Powertrax has attempted to make this Application Guide as accurate as possible. However, Powertrax cannot guarantee correctness. Identical model vehicles may have different axles or differentials than stated in this guide depending on original options ordered and other factors. It is advisable to check the vehicle to determine precisely which differential and axle are present. **IF YOU HAVE ANY QUESTIONS, PLEASE DON'T HESITATE TO CONTACT US AT 800-578-1020.**

## NOTICE REGARDING FRONT AXLE APPLICATIONS:

The Powertrax No-Slip Traction System works well on the front axle of 4-wheel drive vehicles provided a couple of important guidelines are followed. The Powertrax No-Slip Traction System should be used only on vehicles equipped with locking hubs on the front axle or with front axle disconnect. In addition, the vehicle must not be equipped with full time 4-wheel drive. Vehicles equipped with a Powertrax No-Slip Traction System on the front axle should not be operated on the highway with the front hubs locked and 4-wheel drive engaged. Following these guidelines will ensure very on-road driveability while still providing maximum off-road traction.